WALRUS PUMP

Submersible Pump
PW_A Series



To be use with clean water, non-aggressive water and slightly dirty (grey) wastewater.

- To drain the ground water.
- To be application to the sprinkler for vegetations of parks.
- To be used to circulate water in garden ponds.
- To be application to the fishing.

Specifications

Model	PW250A/F	PW400A/F	PW800A
Power (W)	250	400	800
Cycle (Hz)	50	50	50
Voltage (V)	220	220	220
Current (A)	2	3.5	6.8
Max Head (M)	9	10	14
Max Flow Rate (L/min)	160	260	440
Max Suction (M)	5	5	5
Outlet (in.)	1.5	2	2
Cable (M)	6	6	6
Float Switch	F = Yes	F = Yes	No
N.W. (kg)	5.1	8.1	10.5
G.W. (kg)	5.5	8.5	11
Packaging Size (mm)	200*185*350	210*205*400	210*205*400

Feature



The joint Can be removed

1.5"- 2"

Outlet



Float Switch

Water level control, pump will not working in case of no water.
*Only F Model



Have Strainer

prevents debris from clogging the pump



Power Plug

Length 6 meters
Groundwire for more safety



Genuine Copper coil

with Thermal Overload Protection



Pump casing

High polymer plastic

Strong and durable

Dimension



Performance Curve

